




Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!


www.lightplus.uk


Alex LED Down Light is recessed down light with die-cast aluminium body, die-cast aluminium heat sink, solid springs and chrome reflector. COB high power LED chip provides perfect combination of high lighting efficiency, comfortable lighting and humanization design, made by high quality Aluminum profile. The item is very professional and it has all the characteristics to be involved in any kind of architectural or design project, it is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. it is also widely used for public areas, such as stairway, lobby, reception.

Description

Housing - Die Cast Aluminum

Diffuser - PC Diffuser

Reflector - Aluminium Reflector

Color Available - White RAL9010

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC220-240V

Working Temperature - -25C° ~ +50C°


IP Rating - 54

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL175110	10W	LED	1200lm	A115 x B115 x C100mm
LP-DL175120	20W	LED	2400lm	A140 x B140 x C125mm
LP-DL175130	30W	LED	3600lm	A160 x B160 x C145mm
LP-DL175140	40W	LED	4800lm	A198 x B198 x C180mm

Photometrics



Technical Drawing



000