











This pendant offers another option for contemporary indoor lighting solutions. Surrounded by a cylindrical metal structure, with durable white/silver/black powder coat finish, PMMA diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation.

Description

Housing - Metal Powder Coated Finish

Diffuser - PMMA

Reflector - Aluminium Reflector

Color Available - White, Dark-Gray, Black

Lifespan - >50,000 Hours (L80 B10)

Voltage - AC200~240V

Working Temperature - -30C° ~ +65C°


UGR - <19

IP Rating - 65 **IK -** 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-CL244108	08W	LED	1120lm	ASSX B100mm
LP-CL244110	10W	LED	1400lm	A75 X B130mm
LP-CL244115	15W	LED	2100lm	A94 X B150mm
LP-CL244120	20W	LED	2800lm	A115 X B160mm

Photometrics

Technical Drawing



INDOOR LIGHTS CYLINDRO

PENDANT LIGHTS

Kelvin

 $2700 K\,$ – warm white, similar to incandescent bulb


3000K – soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP





OSRAM SAMSUNG

LED DRIVER



OSRAM WW







SERIES WIRING































This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-todate information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk