




Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk



Cova LED Down Light Attractive exclusive down light for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. The light efficiency reach up to 115lm/w with perfect accent lighting performance. That makes it become the priority selected product for commercial lighting. Great cooling fins heat sink design increases the interface between heat sink and air, which makes the heat dissipating performance outstanding and extend the service life of the down light. Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, etc.

Description

Housing - Die-cast Aluminum Body, White Powder Coated

Diffuser - Polycarbonate/PMMA

Reflector - Aluminium Reflector

Color Available - White

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -10°C ~ +50°C

IP Rating - 65


IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL172212	12W	LED	1380lm	A100 X B100 X C26mm
LP-SL172218	18W	LED	2070lm	A145 X B145 X C53mm
LP-SL172220	20W	LED	2300lm	A170 X B170 X C53mm
LP-SL172224	24W	LED	2760lm	A170 X B170 X C54mm

Photometrics



Technical Drawing



000