




Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle




EDA LED with easy installation and best features. This bulkhead light adopts Die-casting aluminum body and 94-v0 fire-rated PC cover. It is also available as led emergency bulkhead are ideal for applications that require continuous light even after a power outage. Modern IP65 rated led bulkhead also provide high bright lighting to stairway, lobby, reception, corridors and building entrances.

Description


Housing - Die cast Aluminum
Diffuser - 94-v0 Fire-rated PC Diffuser
Reflector - Aluminium Reflector
Color Available - White, Black & Dark Gray
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC220-240V
Working Temperature - -10C° ~ +60C°
IP Rating - 65
IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL341012	12W	LED	1440lm	A250 X B40mm
LP-ODL341020	20W	LED	2400lm	A250 X B40mm
LP-ODL341024	24W	LED	2800lm	A250 X B40mm
LP-ODL341036	36W	LED	4320lm	A300 X B40mm

Photometrics



Technical Drawing



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk