




Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle




Rectangular shape LED lighting element and with innovative technology and modern design. It offers outstanding light efficiency and integrates itself through the design into historic and modern surroundings with asymmetrical optics. The LED system offers durability and optimal lumen output.

Description


Housing - Die Cast Aluminium with High Corrosion Resistance
 Powder Coated and Stainless Steel Screws
Diffuser - Thermal-shock Resistant Tempered Glass
Reflector - Aluminum Reflector
Color Available - Grey
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC100~240V
Working Temperature - -20C° ~ +55C°
IP Rating - 66

| Item Code | Power | Lamp | Lumen | Dimensions |
|-------------------|-------|------|---------|-------------------|
| LP-STR315025-H300 | 25W | LED | 3750lm | 200 X 100 X 275mm |
| LP-STR315050-H300 | 2X25W | LED | 7500lm | 200 X 100 X 275mm |
| LP-STR315035-H450 | 35W | LED | 5250lm | 200 X 100 X 275mm |
| LP-STR315070-H450 | 2X35W | LED | 10500lm | 200 X 100 X 275mm |

Photometrics



Technical Drawing



000

LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk