













Compact drive-over and walk over inground Floory LED luminaire designed for illuminating building facades, green areas, parks and outdoor facilities. With the use of high-power LEDs, the in-ground light range provides high luminosity at a low power consumption.

Adapting a double insulation method, all in-ground lights have an IP67 ranking featuring thick tempered glass. Designed to last in extremely harsh environments.

Description

Housing - Body in Aluminum Die-Casting, 316 Grade Stainless Steel Cover in 4mm Thickness

Diffuser - Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box

Reflector - Aluminium Reflector

Color Available - Black

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V

Working Temperature - $-20C^{\circ} \sim +60C^{\circ}$


Heavy Duty - 2000 KG

IP Rating - 67


IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL655001	01W	LED	120lm	A75 X B100mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS FLOORY

UP LIGHTS

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP





OSRAM SAMSUNG

LED DRIVER



OSRAM WWW







SERIES WIRING































This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-todate information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk