



Environmentally friendly alternative to traditional lighting Spike light. Greatly Ideal for uplighting , accent Landscape Lighting. Fixture Solid brass adjustable thumb screw, horizontal rotation 360°.Input low voltage:12V AC/DC,excluding the voltage transformer or connector, 5 Years warranty. Resistant to ambient temperatures up to 60°C.

Description

Housing - Body in Aluminum Die-casting

Diffuser - Clear Frosted Glass, Silicon Rubber Gasket

Reflector - Aluminium Reflector

Color Available - Antique Brass & Black

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC100-240V


Working Temperature - -20C° ~ +55C°

IP Rating - 67


IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL405010	COB 10W	LED	1200lm	A330 X B148 X C100mm
LP-SKL405015	COB 15W	LED	1800lm	A330 X B148 X C100mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS GARDENA

SPIKE LIGHTS

Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk