



Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor




Half Bulk LED, a great looking outdoor light fitting, excellent for lighting your building, ideal for use along walkways, pavements or either side of a doorway and with its opal diffuser, this fitting is perfect installed at any height without risk of glare. Versatile in nature this fitting is ideal for use on with the wall or ceiling with impact-resistant synthetic covers made of polycarbonate. Available in a choice of three fabulous colour finishes, white, Black, or silver grey.

Description


Housing - Die-cast Aluminum
Diffuser - 94-v0 Fire-rated PC diffuser
Reflector - Aluminium Reflector
Color Available - White, Black & Dark-Gray
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC220-240V
Working Temperature - -10C° ~ +50C°
IP Rating - 65
IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL348512	12W	LED	1440lm	A275 X B70mm
LP-ODL348524	24W	LED	2880lm	A275 X B70mm


Photometrics



Technical Drawing




Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk