



Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP

CREE  **PHILIPS**
OSRAM 

LED DRIVER

TRIDONIC  **PHILIPS**
OSRAM 



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk




Hold Light is High quality square shape post top light. It is die cast aluminum body, powder coating and spray lacquer electrostatic anti-aging. This anodized aluminum reflector is protected by a tempered glass which gives it great resistance to corrosion. This luminaire is perfectly designed to be installed vertically in rods of 475 mm in diameter. The specification grade Catapult LED Post Top Light Fixture is designed to work in building perimeter areas and public spaces to compliment a wide variety of architectural styles. LED Area Lights provide high light efficiency with varying light distributions. Outdoor Post Lights create a nostalgic atmosphere and are best applied in parking lots, plazas, shopping malls, gardens, roadways, and areas with pedestrian activity.

Description


Housing - Die-casting Aluminum
Diffuser - Polycarbonate
Reflector - Aluminum Reflector
Color Available - Black, Dark-Gray
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC100-240V
IP Rating - 66
IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-GDL314530	30W	LED	3600lm	A380xB380xC500mm
LP-GDL314540	40W	LED	4800lm	A380xB380xC500mm
LP-GDL314560	60W	LED	7200lm	A475xB475xC530mm
LP-GDL314580	80W	LED	9600lm	A475xB475xC530mm

Photometrics



Technical Drawing



000