



Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP

CREE **BRIDGELUX** **PHILIPS**
OSRAM **SAMSUNG**

LED DRIVER

TRIDONIC **PHILIPS**
OSRAM **MEAN WELL**



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Description

Housing - Die-cast Aluminum
Diffuser - Clear or Frosted Diffuser
Reflector - Aluminium Reflector
Color Available - Black and Gray
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC220-240V
Working Temperature - -30C° ~ +55C°
IP Rating - 44

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL376008	08W	LED	960lm	A350XB120XC120mm
LP-ODL376010	10W	LED	1200lm	A350XB120XC120mm
LP-ODL376012	12W	LED	1400lm	A350XB120XC120mm

Photometrics

Technical Drawing

