



This LED luminaire high efficiency LED system produces high performances of luminous lux with various color temperature illumination.

Description

Housing - Made of Polycarbonate raw material and GRP. shatterproof, radiation protection, UV with high mechanical resistance & with stainless steel Clip.

Diffuser - PMMA Polycarbonate milky anti glare with anti yellowing unbreakable (specially for LED) diffuser. UV stabilized with longitudinal striations for a better control of glare and a high light output.

Reflector - Aluminium Reflector

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


IP Rating - 66

IK - 08


Standards - Designed and manufactured to comply with EN 60598

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL82120	20W	LED	2200lm	1200 x 95 x 75mm
LP-IL82140	40W	LED	4400lm	1200 x 95 x 75mm
LP-IL82160	60W	LED	6600lm	1200 x 95 x 75mm

Photometrics



Technical Drawing




INDOOR LIGHTS PARKY II

INDUSTRIAL LIGHTS

Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk