











This pendant offers another option for contemporary indoor lighting solutions. Surrounded by a cylindrical metal structure, with durable white/silver/black powder coat finish, PMMA diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation

# Description

Housing - Metal Powder Coated Finish

Diffuser - PMMA

Reflector - Aluminium Reflector

Color Available - White, Dark-Grey, Black

**Lifespan -** >50,000 Hours (L80 B10)

Voltage - AC200~240V


Working Temperature - -30C° ~ +65C°

IP Rating - 54


**IK -** 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL232025	25W	LED	3000lm	A360 X B90mm
LP-PL232030	30W	LED	3600lm	A480 X B90mm
LP-PL232036	36W	LED	4320lm	A600 X B90mm
LP-PL232040	40W	LED	4800lm	A600 X B90mm

## **Photometrics**



# **Technical Drawing**



# INDOOR LIGHTS ROUNDY

#### PENDANT LIGHTS

#### Kelvin

 $2700 K\,$  – warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight


6000K - cool white, blue tinted, like a monitor

## Beam Angle



### LED CHIP







OSRAM SAMSUNG

## LED DRIVER



TRIDONIC PHILIPS

OSRAM WW







**SERIES** WIRING































This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-todate information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies Let me know if you'd like assistance tailoring it!



www.lightplus.uk