




### Kelvin

2700K – warm white, similar to incandescent bulb  
3000K – soft white, similar to halogen bulb  
4000K – bright white, similar to fluorescent lighting  
5000K – daylight, very bright & similar to sunlight  
6000K – cool white, blue tinted, like a monitor

### Beam Angle



Solan LED track light with simple structure design. Integrate driver and 3 circuits adapter. Adopt Cree LED and lens for accent lighting. ADC12 aluminum light body provides excellent heat dissipation. Adjustable lighting orientation with 350° in horizontal direction and 90° in vertical direction.

### LED CHIP



### LED DRIVER



### Description

**Housing** - ADC12 Aluminum (White RAL 9016/Black RAL 9005)

**Diffuser** - PC/PMMA Opal Specially for LED.

**Reflector** - Aluminium Reflector

**Color Available** - White, Black

**Lifespan** - >50,000 Hours (L80 B10)


**Voltage** - AC200~240V

**Working Temperature** - -30C° ~ +65C°


**IP Rating** - 20

Item Code	Power	Lamp	Lumen	Dimensions
LP-TL2008	08W	LED	960lm	A196xB46xC180mm
LP-TL2012	12W	LED	1440lm	A196xB46xC200mm
LP-TL2016	16W	LED	1920lm	A196xB46xC200mm

### Photometrics



### Technical Drawing



000

This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



[www.lightplus.uk](http://www.lightplus.uk)