



OUTDOOR LIGHTS STAND

BOLLARD LIGHTS

Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



Double emission bollard & pole for outdoor application. Stand LED light source with a general lighting light distribution is composed of 2 arrayed LEDs, the source luminous flux is 2600lm, nominal luminous efficacy. The device body is made of die-cast aluminium en ab - 46100 and features a grey RAL 7021 finish, processed by means of open pore anodizing + powder coating, the diffuser is made of UV resistant polycarbonate with ingress protection degree is Ip66.

Description

Housing - Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.

Diffuser - PMMA

Reflector - Aluminum Reflector

Color Available - Gray / Dark Gray / Black RAL7021

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC100-240V

IP Rating - 66

LED CHIP



LED DRIVER




This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Photometrics



Technical Drawing

