




Spoty IV attractive down light for prestigious offices, banks, hotels, restaurants, corridors, foyers, sales exhibition and conference rooms as well as residential areas. It is well integrated LED Chip and dimmable phase cut-off or DALI Driver.

Description


Housing - Luminaire Body of die-cast Aluminum White, powder-coated. Luminaire body and Heat Sink form a Compact Unit
Diffuser - Clear Tempered Glass
Reflector - Aluminium Reflector
Color Available - White
Lifespan - >50,000 Hours (L80 B10)
Voltage - AC100~240V
Working Temperature - -35°C ~ +65°C
UGR - <19
IP Rating - 44

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL2038336	3X6W	LED	1980lm	A300 X 8125 X C55mm
LP-DL2038326	2X6W	LED	1320lm	A220 X B125 X C55mm
LP-DL2038316	1X6W	LED	660lm	A125 X B125 X C55mm

Photometrics



Technical Drawing



000


INDOOR LIGHTS SPOTY IV

DOWN LIGHT

Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk