



### Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor


### Beam Angle



### LED CHIP



### LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



[www.lightplus.uk](http://www.lightplus.uk)

### Description

- Housing** - Injection Moulded, in Grey 421C, Vandal Resistant, UV Stabilized, High Mechanical Resistance Due to the Frame Reinforced by Internal Ribbing.
- Diffuser** - Injection Moulded, in V2 self-extinguishing Polycarbonate, UV Stabilized, Clear Polycarbonate, Prismatic Inside for Better Light Control & High Lighting Performance. The External Smooth Finish Facilitates Cleaning, Essential to Maintain Maximum Lighting Efficiency.
- Reflector** - Aluminium Reflector

**Color Available** - Gray 421C

**Lifespan** - >30,000 Hours (L80 B10)

**Voltage** - AC220-240V


**Working Temperature** - -20C° ~ +45C°

**IP Rating** - 66


**IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
L+IND-502020	20W	LED	120lm/W	A600 x B70 x C62mm
L+IND-502030	30W	LED	120lm/W	A1200 x B70 x C62mm
L+IND-502040	40W	LED	120lm/W	A1200 x B70 x C62mm
L+IND-502050	50W	LED	120lm/W	A1500 x B70 x C62mm
L+IND-502060	60W	LED	120lm/W	A1500 x B70 x C62mm

### Photometrics



### Technical Drawing



### Installation Guide

