



Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP

CREE  **PHILIPS**
OSRAM 

LED DRIVER

Light Plus  **TRIDONIC**  **PHILIPS**
OSRAM 



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!


www.lightplus.uk


This solaire powered LED tube light with remote control is an efficient, portable, and eco-friendly lighting solution designed for both indoor and outdoor use. Featuring a high-efficiency solar panel, built-in rechargeable battery, and remote-controlled brightness and timing options, it is ideal for sheds, barns, garages, camping site, parking lots, and off-grid areas. Its waterproof and weather-resistant construction ensures long-lasting performance in all conditions.

Description

Housing - Made in High-Quality aluminum alloy with powder-coated end caps for superior corrosion resistance and durability.

Diffuser - Made in frosted polycarbonate, providing excellent light transmission while minimizing glare.

Color Available - Gray

Reflector - Aluminum Reflector

Voltage - AC200~240V

Working Temperature - -20°C ~ +65°C

Solar Panel - Polysilicone, 6V, 6W 180*270mm | 6V 10W 235*250mm | 6V 15W 350*350mm

LED Type - SMD 2835/0.5W 84PCS | 168 PCS | 252 PCS

Charging Time - 6~8 hours (Under full light)

Working Time - 18-20 hours


Working Mode - Remote Control

IP Rating - 65

IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-IL391030	30W	LED	3600lm	A300 X B45 X C60mm
LP-IL391060	60W	LED	7200lm	A600 X B45 X C60mm
LP-IL391090	90W	LED	10800lm	A900 X B45 X C60mm

Photometrics



Technical Drawing

