



Durable LED bollard for campus paths and residential compounds. A tough polycarbonate lens and die-cast body deliver IK10 impact resistance. Symmetric and wide distributions support comfortable spacing without hotspots. Pre-wired base, anchor bolts, and concealed entry keep the finish neat.

Description

Housing - Die-Cast Aluminum and Extruded Aluminum Pole

Diffuser - Clear PC

Color Available - Black & Grey

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220-240V


Working Temperature - -20C° ~ +65C°

IP Rating - 65


IK - 09

| Item Code | Power | Lamp | Lumen | Dimensions |
|-------------|-------|------|-------|--|
| LP-BL335510 | 10W | LED | 468lm | A120 X B80 X C650 mm A120 X B80 X C800 mm |

Photometrics



Technical Drawing



000

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk