



OUTDOOR LIGHTS GRANITE

BOLLARD LIGHTS



Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor



This LED bollard delivers comfortable pathway lighting with restrained glare and clean cut-off. The sealed optic and weather-rated gaskets keep moisture and dust out. Offered with symmetric or forward-throw distributions to keep light where it is needed. Root or surface mounting options simplify installation on new builds or refurbishment.

Description

Housing - Die-Cast Aluminum and Extruded Aluminum Pole

Diffuser - Frost PC

Color Available - Black & Grey

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220-240V


Working Temperature - -20°C ~ +65°C

IP Rating - 54


IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334406	06W	LED	170lm	A80 X B120 X C400 mm
LP-BL33442X6	2x6W	LED	170lm	A80 X B120 X C650 mm
LP-BL33442X10	2x10W	LED	170lm	A80 X B120 X C800 mm

Photometrics



Technical Drawing



000

LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk