




Reliable LED bollard for mixed-use developments and hospitality. The heavy-duty construction and UV-stable coating handle heat and sun exposure. Optional sensor packages enable dusk-to-dawn operation or presence-based dimming. All fixings are concealed for a clean finish.

Description


Housing - Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser - Opal PC
Color Available - Black & Grey
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC220-240V
Working Temperature - -20°C ~ +65°C
IP Rating - 65
IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL336812	12W	LED	705lm	AØ120 X B470 X C800 mm AØ120 X B620 X C1000 mm

Photometrics



Technical Drawing



Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk