



A Harbour LED bollard for pedestrian routes, courtyards, and hotel gardens. The housing is die-cast aluminum with UV-stable powder coating, and the impact-resistant lens protects the optics. Choose opal or clear lenses with optional louvres for comfort. Integral control gear, surge protection, and stainless hardware ensure reliable, low-maintenance operation.

## Description

**Housing** - Die-Cast Aluminum and Extruded Aluminum Pole

**Diffuser** - Clear PC

**Color Available** - Black & Grey

**Lifespan** - >50,000 Hours (L90 B10)

**Voltage** - AC220~240V


**Working Temperature** - -20C° ~ +65C°

**IP Rating** - 54


**IK** - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334306	06W	LED	268lm	A120 X B80 X C400 mm A120 X B80 X C650 mm A120 X B80 X C800 mm

## Photometrics



## Technical Drawing



## OUTDOOR LIGHTS HARBOUR

### BOLLARD LIGHTS

## Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

## Beam Angle



## LED CHIP



## LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



[www.lightplus.uk](http://www.lightplus.uk)