



A clean cylindrical LED bollard that complements modern landscaping. The powder-coated aluminum enclosure resists UV fade and corrosion. Clear, prismatic, or opal optics deliver uniform light with minimal glare. Serviceable gear tray and stainless-steel fasteners make maintenance straight forward.

Description

Housing - Die-Cast Aluminum and Extruded Aluminum Pole

Diffuser - Tempered Clear Glass

Color Available - Black & Grey

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220-240V


Working Temperature - -20C° ~ +65C°

IP Rating - 65


IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335210	10W	LED	562lm	A120 X B370 mm
				A120 X B650 mm
				A120 X B1000 mm
LP-BL335215	15W	LED	843lm	A120 X B370 mm
				A120 X B650 mm
				A120 X B1000 mm

Photometrics



Technical Drawing



000

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

000