



Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A Oxford LED bollard for pedestrian routes, courtyards, and hotel gardens. The housing is die-cast aluminum with UV-stable powder coating, and the impact-resistant lens protects the optics. Choose opal or clear lenses with optional louvres for comfort. Integral control gear, surge protection, and stainless hardware ensure reliable, low-maintenance operation.

LED CHIP



LED DRIVER




Description


- Housing** - Die-Cast Aluminum and Extruded Aluminum Pole
- Diffuser** - Clear PC
- Color Available** - Black & Grey
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220-240V
- Working Temperature** - -20C° ~ +65C°
- IP Rating** - 54
- IK** - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334206	06W	LED	268lm	A80 X B120 X C400 mm
				A80 X B120 X C650 mm
				A80 X B120 X C800 mm
LP-BL33422X6	2x6W	LED	268lm	A80 X B120 X C400 mm
				A80 X B120 X C650 mm
				A80 X B120 X C800 mm

Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!

