



Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A square-profile LED bollard with crisp edges and a minimal cap. The sealed module maintains output over time by keeping contaminants out. Symmetric and wide distributions simplify layout across varied path widths. Optional louvers and house-side shields help control spill.

LED CHIP



LED DRIVER




Description

- Housing** - Die-Cast Aluminum and Extruded Aluminum Pole
- Diffuser** - Clear Glass
- Color Available** - Black & Grey
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220-240V
- Working Temperature** - -20C° ~ +65C°
- IP Rating** - 65
- IK** - 09




Item Code	Power	Lamp	Lumen	Dimensions
LP-BL337410	10W	LED	682lm	A150 X B150 X C650 mm
LP-BL337420	20W	LED	1063lm	A150 X B150 X C800 mm
LP-BL337430	30W	LED	2046lm	A150 X B150 X C1000 mm

Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!

