



Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor

Beam Angle



A square-profile LED bollard with crisp edges and a minimal cap. The sealed module maintains output over time by keeping contaminants out. Symmetric and wide distributions simplify layout across varied path widths. Optional louvers and house-side shields help control spill.

LED CHIP



LED DRIVER



Description

Housing - Die-Cast Aluminum and Extruded Aluminum Pole

Diffuser - Clear Glass

Color Available - Black & Grey

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220-240V


Working Temperature - -20C° ~ +65C°

IP Rating - 65


IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL336610	10W	LED	682lm	A110 X B110 X C400 mm A110 X B110 X C650 mm A110 X B110 X C800 mm A110 X B110 X C1000 mm
LP-BL336615	15W	LED	1023lm	A110 X B110 X C400 mm A110 X B110 X C650 mm A110 X B110 X C800 mm A110 X B110 X C1000 mm

Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk