



## ALUMINUM PROFILES

### FLEXIL I

#### Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

#### Beam Angle



IP67 flexible LED light line with a 12mm cross section. UV resistance, chemical stability against urban gases and protection against abrasion. Vertical bending only, excellent solution for indoor/outdoor organic facade accent lighting or decorative applications requiring IP67 ingress.

#### LED CHIP



#### LED DRIVER



#### Description

**Housing** - PCB anti-yellowing & heat resistance silicone glue extrusion chemical resistance acid.

**Diffuser** - Milky White Silicone

**Color Available** - Milky

**Lifespan** - >50,000 Hrs (L80 B10)

**Voltage** - DC 24V

**Working Temperature** - -20°C ~ 60°C

**IP Rating** - 67


**IK** - 08



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!

#### Photometric



#### Technical Drawing

