



Wally Recessed for outdoor applications, drive-over up to 2500 kg, recessed ground body in aluminium, trim in AISI 316L stainless steel or aluminium, screen in tempered, transparent extra-clear glass, screen in tempered, serigrapher extra-clear glass (diffuse optics) finishes stainless steel, ingress protection: IP67 impact resistance: IK10.

Wally family is strict compliance with the global quality standards.

## Description

**Housing** - Made of 316 Stainless Steel

**Diffuser** - Tempered Glass Diffuser

**Reflector** - Aluminium Reflector

**Color Available** - Black

**Lifespan** - >50,000 Hours (L90 B10)

**Voltage** - AC220~240V

**Working Temperature** - -20C° ~ +65C°


**Heavy Duty** - 2000 KG

**IP Rating** - 67


**IK** - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL653703	3x1W	LED	360lm	A100 x B108mm
LP-UL653709	9x1W	LED	1080lm	A160 x B110mm
LP-UL653718	18x1W	LED	2160lm	A210 x B120mm

## Photometrics



## Technical Drawing



000

## OUTDOOR LIGHTS WALLY

### UP LIGHTS

## Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

## Beam Angle



## LED CHIP



## LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



[www.lightplus.uk](http://www.lightplus.uk)