



Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk




Down LED Down Light Attractive exclusive down light for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. The light efficiency reach up to 120lm/w with perfect accent lighting performance. That makes it become the priority selected product for commercial lighting. Great cooling fins heat sink design increases the interface between heat sink and air, which makes the heat dissipating performance outstanding and extend the service life of the down light. Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, etc.

Description

- Housing** - Die-cast aluminum body
- Diffuser** - Tempered Clear Glass
- Reflector** - Aluminium Reflector
- Color Available** - White
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220~240V
- Working Temperature** - -10C° ~ +50C°
- IP Rating** - 54
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL172007	07W	LED	840lm	A92 x B50 x C75mm
LP-DL172012	12W	LED	1440lm	A135 x B56 x C110mm
LP-DL172015	15W	LED	1800lm	A165 x B63 x C145mm
LP-DL172020	20W	LED	2400lm	A190 x B65 x C170mm
LP-DL172030	30W	LED	3600lm	A230 x B70 x C220mm

Photometrics



Technical Drawing

