




Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk




This focused lighting solution is crafted from robust die-cast aluminum with a protective, high-quality finish, ensuring long term durability and resistance to typical indoor wear. Designed for recessed ceiling installation, it combines a sleek, discreet aesthetic with powerful, energy-efficient LED illumination, enhancing indoor spaces with both elegance and reliable performance.

Description

- Housing** - Die Cast Aluminum, Highly pure powder coating
- Diffuser** - Optical PMMA Lens
- Reflector** - Aluminum Reflector
- Color Available** - White, Black, Silver & Grey
- Lifespan** - >50,000 Hours (L80 B10)
- Voltage** - AC220~240V
- Working Temperature** - -30C° ~ +65C°
- IP Rating** - 54

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL918415	15W	LED	1800lm	A105 X B42 mm
LP-DL918420	20W	LED	2400lm	A136 X B50 mm
LP-DL918430	30W	LED	3600lm	A162 X B58 mm
LP-DL918440	40W	LED	4800lm	A213 X B66 mm

Photometrics



Technical Drawing

